SECRET

1968 FEB 6 21 45 Z

OUT 64260

| , . | 2132Z FEB 68 CITE | 2916 | | 25X1 25X1 |
|--|--|--|---|---------------|
| 1. IT IS RI "INSTRUCTIONS I PHOTOGRAPHY" AS NEGATIVE ON EAC IS USED AS THE BETWEEN THE HEA EACH ROLL, IT S TO PREVENT THE IDENT FROM TOUG ON THE SPOOL. | OF THE UNIVERSAL GRIE EQUESTED THAT THE FOR THE USE OF THE UNIVERSAL PART OF CH ROLL OF PHOTOGRAPH MISSION SENSOR. THE AD IDENT AND THE FIRS SHOULD BE OF SUFFICING SPLICE BETWEEN THE I CHING THE NEGATIVE WI THE INSTRUCTION SHOU | BE DIRECTED TO INCL NVERSAL GRID WITH IN FITHE HEAD IDENT OF HY IN WHICH THE 11S E INSTRUCTION SHOUL ST FRAME OF PHOTOGR ENT LENGTH (15 TO I INSTRUCTION AND THE HEN THE NEGATIVE IS JLD BE RIGHT READIN | UDE THE 115-A THE ORIGINAL 5-A CAMERA LD BE SPLICED RAPHY ON 18 INCHES) E HEAD 5 ROLLED | 25X1 |
| 2. INSTRUC | THE HEAD IDENT IS RICIONS WERE FORMATED | AND COPIED AT | 100 | 25 X 1 |
| NEGATIVES AND | POSITIVES WERE SENT TO | FOR REPRODU | | 25X1 225X1 |
| AS FOLLOWS: | FILM WITH THE TITLING SPEED INDICATOR MI | NG READABLE: THE CL | OCKS. GEO- | |
| ALONG THE BOTTO BLOCK IS TO THE THE DATA BLOCK CAMERA). READ TO THE RIGHT AN | 2916 S E C R E T HE LOWER LEFT CORNER OM EDGE OF THE FILM, E RIGHT ON ODD NUMBER IS TO THE LEFT ON EV AND REPORT COORDINAT ND UP. X-35.2/Y-8.4 IS THE | NOT THE FORMAT. T RED FRAMES (FWD CAN VEN NUMBERED FRAMES TES IN THE NORMAL N | THE DATA MERA). S (AFT MANNER, | 25X1 |
| END | OF MESSAGE | | Cy No. Office Action | |
| | | | File Cable Sec. | 25 X 1 |
| | | | 2728 | |
| | | | 17700 | |
| | | | Security | |
| | | A STATE OF THE STA | 755G | |
| | | | 75 153 | |
| | | | 156 | |
| | | | | |
| | | | 014.02-4 | |
| | | | (572.0) | 25 Y 1 |

SECRET

Advance Copy Sanitized With Text

DIA-AP

Approved For Release 2008/07/31 : CIA-RDP78B04549A000100020028-5